


FIG. 1





Rec'd PCT/PTO 1 5 MAR 2005




Rec'd PCT/PTO 1 5 MAR 2005












FIG. 9




FIG. 10





FIG. II




8/12

PCT/US2003/029981

Rec'd PCT/PTO 15 MAR 2005

FIG. 12



9/12

PCT/US2003/029981
Rec'd PCT/PTO 15 MAR 2005




FIG. 14




FIG. 158 OF THE SUM OF THE MULTIPLIER TAKES THE SOUARE ROOT ADS34 ANALOG TWO SQUARED INPUT SIGNALS OP27 SUMMING AMP SURS THE 2 SQUARED OC SIGNALS SQUARE IT WITH A AD633JN SQUARE IT WITH A AD633JN THE DC VOLTAGE AT THIS THE DC VOLTAGE AT THIS POINT CAN BE POSITIVE POINT CAN BE POSITIVE ANALDG MULTIPLIER OR NEGATIVE SO WE OR NEGATIVE SO WE AHALOG MULTIPLIER A GAIR ADJUST 10X TO 80X SAGAIR ADJUST 10X TO 80X A PGA205 X8 DC AMPLIFIER ATTENUATOR FOLLOWED BY ATTENUATOR FOLLOWED BY **WARIABLE GAIN 10X TO 80X** A PGA205 X8 DC AMPLIFIER VARIABLE GAIN 10X TO 80X SSMZD18T YARIABLE SSA2D18T VARIABLE FIG. 15A THIS TAKES OUT THE TRANSMITTER "BIAS" FROM IHIS TAKES OUT THE TRANSMITTER "BIAS" FROM THIS ADJUSTMENT ZERO'S THE PGA 204 OUT FHIS ADJUSTMENT ZERO'S THE PGA 204 OUT WITH THE LOCATOR POINTED TO THE SKY IN WITH THE LOCATOR POINTED TO THE SKY THE DIRECT SIGNAL THE DIRECT SIGNAL KIO DC OUT 8 AMPLIFIER AMPLIFIER XIODC PGA 204 PGA 204 CALIBRATE 💌 CALIBRATE, OUTPUT IS A LINEAR DC VOLTAGE WITH A DC YOLTAGE WITH A CONVERSION GAIN **DUTPUT IS A LINEAR** CONVERSION GAIN OF 7.SV/V RINS TRUPOWER DET TRUPOWER DET OF 7.5V/V RIKS AD8361 AD8361 RECEIVER 2 )(QDI834 901 LOG PERIODIC RECEIVER ) ANTERNA AHTENNA

